

# Specifications

09/04/2024

Project  
Roots Coffee Co.  
9805 S. YODER ROAD  
YODER, KS

From  
Pintail Food Service Consulting  
LLC  
Tanner Erdman  
611 E. Central Ave.  
Wichita, KS 67202

## ITEM 1 - SHELVING PACKAGE (6 REQ'D)

### Quantum

Composed of the following

- 1 kt Model WR86-2472GY-5 Wire Shelving Starter Kit, 72"W x 24"D x 86"H, 600 - 800 lb. capacity, includes (5) wire shelves & (4) posts, gray epoxy antimicrobial finish, NSF, shipped KD
- 1 kt Model WR86-2454GY-5 Wire Shelving Starter Kit, 54"W x 24"D x 86"H, 600 - 800 lb. capacity, includes (5) wire shelves & (4) posts, gray epoxy antimicrobial finish, NSF, shipped KD
- 1 kt Model WR86-2430GY-5 Wire Shelving Starter Kit, 30"W x 24"D x 86"H, 600 - 800 lb. capacity, includes (5) wire shelves & (4) posts, gray epoxy antimicrobial finish, NSF, shipped KD
- 1 kt Model WR86-2436GY-5 Wire Shelving Starter Kit, 36"W x 24"D x 86"H, 600 - 800 lb. capacity, includes (5) wire shelves & (4) posts, gray epoxy antimicrobial finish, NSF, shipped KD
- 2 kt Model WR86-2442GY-5 Wire Shelving Starter Kit, 42"W x 24"D x 86"H, 600 - 800 lb. capacity, includes (5) wire shelves & (4) posts, gray epoxy antimicrobial finish, NSF, shipped KD
- 1 ea 15 year limited warranty (limited against rust and corrosion)

---

## ITEM 2 - THREE (3) COMPARTMENT SINK (1 REQ'D)

### Advance Tabco Model FC-3-1824-18RL Dimensions: 43(h) x 90(w) x 30(d)

Fabricated Sink, 3-compartment, 18" right & left drainboards, bowl size 18" x 24" x 14" deep, 16 gauge 304 stainless steel, tile edge splash, rolled edge, 8" OC faucet holes, stainless steel legs with adjustable side cross-bracing, 1" adjustable stainless steel bullet feet, overall 30" F/B x 90" L/R, NSF

- 1 ea T&S Brass Model B-0133-ADF12 EasyInstall Pre-Rinse Unit, with mixing faucet, wall mount base, 8" centers, B-0044-H stainless steel flexible hose with polyurethane inner hose, overhead spring body & (B-0107) spray valve, 18" riser, add-on faucet with (062X) 12" swing nozzle, Eterna cartridges with spring checks, lever handles, 1/2" NPT female inlets

---

## ITEM 3 - WALL GRID SHELVING UNIT (2 kt REQ'D)

### Quantum Model SGK-403036-2GY

Store Grid Standard-Duty Kit, includes: (1) 40" wall track, (1) 30" x 36" grid panel, (1) 18"W x 36"L large shelf, (1) 17"L x 7"W x 5"H basket, (2) 6" hook, (10) small hook, (1) 9"W x 18"L small shelf, (1) single bin holder, (1) QUS230 bin (available in blue, black, ivory, red, yellow and black) and (1) wall tack mounting bracket, black epoxy antimicrobial finish, NSF

**ITEM 4 - DISHWASHER, UNDERCOUNTER (1 REQ'D)****Jackson WWS Model DISHSTAR HT Dimensions: 33.31(h) x 24.25(w) x 25(d)**

DishStar® Dishwasher, undercounter, 24-1/4"W, high temperature sanitizing with built-in 70°rise booster heater, approximately (24) racks/hour, (1.1) gallons of water per rack, universal timer, built-in chemical pumps, auto-fill, stainless steel wash pump, cabinet finished in stainless steel, 1 HP, ETL-Sanitation, cETLus

- 1 ea 1 year parts & labor warranty, continental USA, standard
- 1 ea 208v/60/1-ph, 37.2 amps
- 1 ea Model 04820-100-04-07 Pressure Regulator, 1/2"

**ITEM 5 - SOILED DISHTABLE (1 REQ'D)****Advance Tabco Model DTU-U60-48L Dimensions: 44.5(h) x 48(w) x 30(d)**

Dishtable, undercounter, 48"W x 30"D x 44-1/2"H, 16 gauge 304 stainless steel top with rolled rims, 20" x 20" x 5" deep sink bowl on left, 10-1/2"H backsplash, stainless steel legs with welded cross bracing & stainless steel adjustable bullet feet, NSF

- 1 ea T&S Brass Model B-0133-R EasyInstall Pre-Rinse Unit, 33-7/16"H, 8" centers, wall mount base, spring action, PVC hose, quarter-turn Eterna cartridges, low lead

**ITEM 6 - REACH-IN REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MBF8005GR Dimensions: 81.3(h) x 51.7(w) x 31.7(d)**

Atosa Refrigerator, reach-in, two-section, 51-7/10"W x 31-7/10"D x 81-3/10"H, top mount self-contained refrigeration, 43.2 cu. ft. (2) locking hinged solid doors, digital temperature control, 33° to 40°F temperature range, (6) adjustable shelves, interior LED lighting, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 4" casters, R290 Hydrocarbon refrigerant, 1/5 HP, 115v/60/1-ph, 3.2 amps, cord with NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

- 1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 7 - REACH-IN REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MBF8005GR Dimensions: 81.3(h) x 51.7(w) x 31.7(d)**

Atosa Refrigerator, reach-in, two-section, 51-7/10"W x 31-7/10"D x 81-3/10"H, top mount self-contained refrigeration, 43.2 cu. ft. (2) locking hinged solid doors, digital temperature control, 33° to 40°F temperature range, (6) adjustable shelves, interior LED lighting, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 4" casters, R290 Hydrocarbon refrigerant, 1/5 HP, 115v/60/1-ph, 3.2 amps, cord with NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

- 1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 8 - MOP SINK & FAUCET**

Provided by Plumbing subcontractor

**ITEM 9 - SHELVING, WALL MOUNTED (1 REQ'D)****Advance Tabco Model K-246 Dimensions: 7.5(h) x 36(w) x 8(d)**

Utility Shelf, wall-mounted, 36"W x 8"D, 1-1/2" upturn on rear & sides, (3) mop holders, (4) rag hooks, stainless steel, NSF

**ITEM 10 - R O SYSTEM (1 REQ'D)****OptiPure Model OPS70CR-16**

Provided by owner's vendor

---

**ITEM 11 - ICE MAKER, CUBE-STYLE (1 REQ'D)****Hoshizaki Model KML-500MAJ Dimensions: 22(h) x 30(w) x 27.38(d)**

Ice Maker, Cube-Style, 30"W, air-cooled, self-contained condenser, production capacity up to 442 lb/24 hours at 70°/50° (400 lb AHRI certified at 90°/70°), stainless steel finish, crescent cube style, R-404A refrigerant, 115v/60/1-ph, 7.6 amps, NSF, UL

- 1 ea Warranty: 3-Year parts & labor on entire machine
  - 1 ea Warranty: 5-Year parts & labor on evaporator
  - 1 ea Warranty: 5-Year parts on compressor & air-cooled condenser
  - 1 ea Model B-500SF Ice Bin, 30"W, top-hinged front-opening door, 500-lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, painted legs included, protected with H-GUARD Plus Antimicrobial Agent, ETL, ETL-Sanitation
  - 1 ea Warranty: 3-Year parts & labor for bin
  - 1 ea Model H9320-51 Water Filtration System, single configuration, 18.4" H (manifold & cartridge)
  - 1 ea Warranty: 1-Year on entire water filtration system & replaceable elements, standard
- 

**ITEM 12 - HAND SINK (1 REQ'D)****Advance Tabco Model 7-PS-EC-SP-X Dimensions: 13(h) x 18(w) x 16(d)**

Special Value Hand Sink with 7-3/4" side splashes, wall model, 14" wide x 10" front-to-back x 5" deep bowl, 304 stainless steel construction, splash mounted faucet, 1-1/2" basket drain, wall bracket, NSF

---

**ITEM 13 - REACH-IN FREEZER (1 REQ'D)****Atosa USA, Inc. Model MBF8002GR Dimensions: 81.3(h) x 51.7(w) x 31.7(d)**

Atosa Freezer, reach-in, two-section, 51-7/10"W x 31-7/10"D x 81-3/10"H, top mount self-contained refrigeration, 43.2 cu ft., (2) locking hinged solid doors, digital temperature control, -8° to 0°F temperature range, (6) adjustable shelves, interior LED lighting, automatic evaporation, electric defrost, stainless steel interior & exterior, galvanized steel back, 4" casters, R290 Hydrocarbon refrigerant, 3/4 HP, 115v/60/1-ph, 8.6 amps, cord with NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

- 1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)
- 

**ITEM 14 - SHELVING, WALL MOUNTED (1 REQ'D)****Advance Tabco Model WS-15-108-16 Dimensions: 13.5(h) x 108(w) x 15(d)**

Shelf, wall-mounted, 108"W x 15"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 16/304 satin finish stainless steel, NSF (units 84" & longer have (3) support brackets)

MODIFIED IN LENGTH AS PER PLAN

---

**ITEM 15 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-303 Dimensions: 37(h) x 36(w) x 30(d)**

Work Table, 36"W x 30"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

**ITEM 16 - RAPID COOK OVEN (1 REQ'D)****Merrychef USA Model E1S Dimensions: 23.2(h) x 16(w) x 22.6(d)**

eikon® Microwave Convection/Impingement Oven, ventless, 12" cooking cavity, EasyTouch™ controls, USB memory, bottom-hinged door, built-in catalytic converter, includes: (1) flat cook plate "DC0322", (1) guarded pizza paddle "SR318", (1) sold base basket "32Z4080" & (1) cook plate liner "32Z4088", black exterior, stainless steel construction, 208/240v/60/1-ph, NEMA 6-15P, UL

1 ea 1 year parts & labor warranty, standard

**ITEM 17 - SANDWICH / SALAD PREPARATION REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MSF8301GR Dimensions: 41.38(h) x 27.5(w) x 30(d)**

Atosa Sandwich/Salad Top Refrigerator, one-section, 27-1/2"W x 30"D x 41-3/8"H, includes (8) 1/6 poly pans, rear-mounted, self-contained refrigeration, 7.2 cu. ft., (1) solid hinged self-closing door, digital temperature control, 33° to 40°F temperature range, (1) adjustable shelf, 9-1/4" poly cutting board, ventilated refrigeration, automatic automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 3" casters, R290 Hydrocarbon refrigerant, 1/7 HP, 115v/60/1-ph, 2.3 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

1 ea 1/6 size, 6" deep poly pans and dividers included

**ITEM 18 - UNDERCOUNTER REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MGF36RGR Dimensions: 34.25(h) x 36.31(w) x 30(d)**

Atosa Undercounter Refrigerator, reach-in, two-section, 36-5/16"W x 30"D x 34-1/4"H, rear-mounted self-contained refrigeration, 8.7 cu. ft., (2) hinged solid doors, digital temperature control, 33° to 40°F temperature range, (2) adjustable shelves, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 2" casters, R290 Hydrocarbon refrigerant, 1/7 HP, 115v/60/1-ph, 2.3 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 19 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-307 Dimensions: 37(h) x 84(w) x 30(d)**

Work Table, 84"W x 30"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

MODIFIED IN LENGTH AS PER PLAN

**ITEM 20 - SHELVING, WALL MOUNTED (2 REQ'D)****Advance Tabco Model WS-15-48 Dimensions: 13.5(h) x 48(w) x 15(d)**

Shelf, wall-mounted, 48"W x 15"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 18/430 satin finish stainless steel, NSF

**ITEM 21 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-307 Dimensions: 37(h) x 84(w) x 30(d)**

Work Table, 84"W x 30"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

Provision for drop-in equipment

MODIFIED IN LENGTH AS PER PLAN

---

**ITEM 22 - ICE & WATER DISPENSER (1 REQ'D)****BK Resources Model BK-DIWSBL-2118X-P-G Dimensions: 13(h) x 18(w) x 21(d)**

Ice & Water Unit, drop-in, 18"W x 21"D O.A., ice bin with 11" deep liner & removable sliding cover, water filler station with BKF-SGF-G faucet & perforated insert, includes BKDR-325CP & BKDR-15CP drains, 304 stainless steel construction, 17-1/8" x 20" cutout recommended, lead free, NSF

---

**ITEM 23 - UNDERCOUNTER REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MGF8403GR Dimensions: 34.25(h) x 60.25(w) x 30(d)**

Atosa Undercounter Refrigerator, reach-in, two-section, 60-1/4"W x 30"D x 34-1/4"H, rear-mounted self-contained refrigeration, 17.2 cu. ft., (2) hinged solid doors, digital temperature control, 33° to 40°F temperature range, (2) adjustable shelves, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 2" casters, R290 Hydrocarbon refrigerant, 1/5 HP, 115v/60/1-ph, 2.8 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

---

**ITEM 24 - SHELVING, WALL MOUNTED (1 REQ'D)****Advance Tabco Model WS-15-108-16 Dimensions: 13.5(h) x 108(w) x 15(d)**

Shelf, wall-mounted, 108"W x 15"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 16/304 satin finish stainless steel, NSF (units 84" & longer have (3) support brackets)

MODIFIED IN LENGTH AS PER PLAN

---

**ITEM 25 - BLENDER, BAR (2 REQ'D)****Blendtec Model C825C11Q-A1DA1A Dimensions: 18.7(h) x 9(w) x 9(d)**

Connoisseur 825™ Blender Package, countertop or in-counter, (1) 75 oz FourSide™ jar with measurements up to 32 oz., includes: soft lid, small 3" wingtip blade, BPA Free Tritan™ container, 30 pre-programmed blend cycles, 5 programmable cycle buttons and pulse, removable sound enclosure, 3.8 HP (peak), 15 amp, 1800 watt direct drive motor, 120v/50/60/1-ph, black, ETL, NSF

2 ea 3 year warranty on parts & 1 year warranty on labor (standard)

---

**ITEM 26 - DROP-IN REFRIGERATED WELL (1 REQ'D)****Hatco Model CWB-2-120-QS Dimensions: 25.5(h) x 32(w) x 27(d)**

(QUICK SHIP MODEL) Drop-In Refrigerated Well, (2) pan size, top mount, electronic temperature control, pan support bars for full-size pans, condenser unit (can be rotated), sight glass, service valves, dryer/filter, insulated with drain, aluminized steel housing, stainless steel bezel, 1/4 HP, 120v/60/1-ph, NEMA 5-15P, cULus, Made in USA

1 ea NOTE: Sale of this product must comply with Hatco's Minimum Resale Price Policy; consult order acknowledgement for details

1 ea NOTE: Includes 24/7 parts & service assistance, call 414-671-6350

1 ea One year parts & labor warranty, standard

1 ea Model CWB-EWC Four year extended parts only warranty on the compressor (available at time of purchase only)

1 ea CE mark not available

**ITEM 27 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-249 Dimensions: 37(h) x 108(w) x 24(d)**

Work Table, 108"W x 24"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

- 1 ea Model TA-61 Modification to reduce length and/or width of table, start with next largest size then add "TA-61" to model number  
Provision for drop-in equipment
- 1 ea Krowne Model KR-D24 Drip Tray Trough, drop-in, 24"W x 14"D, stainless steel perforated inserts, 1-1/2" drain, includes mounting studs, stainless steel construction, (22"W x 12"D cutout required), NSF

**ITEM 28 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-305 Dimensions: 37(h) x 60(w) x 30(d)**

Work Table, 60"W x 30"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

- 1 ea Weld-In sink - single bowl
- 1 ea Model TA-11F Sink Welded Into Table Top, 10"W x 14"D x 10" deep bowl, includes faucet, NSF (must specify sink location)  
Provision for drop-in equipment

**ITEM 29 - DRIP TROUGH (1 REQ'D)****Micro Matic USA Model DP-120DGR**

Drip Tray Trough, surface mount, 12"W x 5"D, integral glass rinser (NSF-certified), louvered stainless steel screen, 5/8" O.D. drain, stainless steel construction

**ITEM 30 - COFFEE GRINDER (1 REQ'D)****F&O Imports Model GH2 Dimensions: 26(h) x 7(w) x 17(d)**

Mahlkonig GH2 Coffee Grinder, 4.4 lb hopper capacity, 85 mm vertical grinding discs, stepless adjustable grind settings, adjustable spout with bag holder, finger protection, black plastic housing, 1600 RPM, 100-115v/60/1-ph, 750 watts, CE, ETL, NSF

- 1 ea Provided by owner's vendor

**ITEM 31 - ESPRESSO CAPPUCCINO MACHINE (1 REQ'D)****Franke Coffee Systems Model S700 Dimensions: 29.5(h) x 13.4(w) x 26.3(d)**

(REPLACES MODEL: EVOLUTION) S700 Espresso Machine, semi-automatic, 2-step, (3) boiler, up to 250 cups per day, (2) lockable bean hoppers: (1) 4.4lbs. capacity hopper & (1) 1.3lbs capacity hopper, (2) adjustable grinders, 50mm brewing system, with iQ Flow, 8" touch screen with intuitive menu, steam wand, hot water dispenser, 208v/60/1-ph, 30 amps, 4.8-5.8kW, 2L-PE, L6-30P, cETLus, ETL-Sanitation

- 1 ea Note: All prices quoted are valid for 30 days from the date stated on the quotation
- 1 ea Model IQFLOW Define taste profiles and shot times for each product independently. Each taste profile is real time assured by iQFlow. No grinder readjustments needed.
- 1 ea Model S3 ASP Autosteam Pro S3 steam wand (automatic temperature and foam shut off)
- 1 ea Machine install, startup and calibration of equipment by Franke authorized service partner (NET price, no additional discount available)
- 1 ea Model INSTALL KIT Installation Kit, includes: water hose and BSP connector, technical support sticker, water hardness test strip, MSDS sheets for cleaning tablets and milk cleaner (included in installation cost)
- 1 ea 12 month parts & labor warranty, standard
- 1 ea Water filtration kit (includes VIVREAU filter cartridge, filter head, fittings, water test kit).
- 1 ea Shipping from Franke Smyrna, TN 37167 (NET price, no additional discount available) (NET)
- 3 ea Model MILK DETERGENT Milk detergent, 1 liter bottle (3 months of cleanings)

- 1 ea Model CLEANING SUPPLIES SUBSCRIPTION Cleaning supplies subscription information - see flyer in documents or go to <http://frankecoffeessystemsorders.com>
- 1 ea Provided by owner's vendor

**ITEM 32 - UNDERCOUNTER REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MGF8402GR Dimensions: 34.25(h) x 48.25(w) x 30(d)**

Atosa Undercounter Refrigerator, reach-in, two-section, 48-1/4"W x 30"D x 34-1/4"H, rear-mounted self-contained refrigeration, 13.38 cu. ft., (2) hinged solid doors, digital temperature control, 33° to 40°F temperature range, (2) adjustable shelves, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 2" casters, R290 Hydrocarbon refrigerant, 1/7 HP, 115v/60/1-ph, 2.3 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

- 1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 33 - COFFEE BREWER (1 REQ'D)****Curtis Model G4TP1T10A3100 Dimensions: 24.75(h) x 20.13(w) x 20.75(d)**

Thermopro® G4 Coffee Brewer, twin, 1 gallon capacity, batch selectable, 15 to 21 gallons per hour, 5.2 gallon tank volume, 4.3" touch screen, icon-driven interface streamlines operation, on-screen instructions, built-in self diagnostic system with energy saving mode, advanced scale warning system, Gold Cup® series, stainless steel, 220v/50/60/1-ph, 5100/7600 watts, 23/34.5 amps, 2 GPM, 3W+G, 20-90 psi, 3/8" flare fitting, cULus, NSF

- 1 ea Provided by owner's vendor

**ITEM 34 - DISPLAY CASE, REFRIGERATED/NON-REFRIG (1 REQ'D)****Structural Concepts Model HMBC4 Dimensions: 56.25(h) x 51(w) x 34.13(d)**

Harmony® Service/Self-Service Bakery Merchandiser, 51W, upper: lift-up curved glass, clear glass rear sliding doors, lighted glass shelf in upper display, convertible refrigeration, center divided display area, lower: open self-service refrigerated, top light, black interior, black trim, (2) cutaway end panels, Breeze with EnergyWise self-contained refrigeration system, cETLus, ETL-Sanitation

- 1 ea NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 1 ea NOTE: 35" minimum entry door clearance required (without shipping skid)
- 1 ea 1 yr. parts & labor warranty, 5 yr. compressor warranty, standard
- 1 ea Self-contained refrigeration system, standard
- 1 ea 120/230v/60/1ph, 9.68 amps, 3-wire plus ground required, standard
- 1 ea 6 ft straight blade power cord with NEMA 14-20P (self-contained), standard
- 1 ea NOTE: Compressor air intake from rear & out front panel, front panel cannot be blocked (Not applicable with remote refrigeration option)
- 1 ea Base Support: Units are supplied with levelers extended 1-1/4" & MUST be adjusted during installation to ensure unit is level for operation
- 1 ea Exterior: Laminate standard color 909-58 Black
- 1 ea Rear Exterior: White, painted standard
- 1 ea Trim: Black, standard
- 1 ea Upper rear: Clear glass sliding rear doors, standard
- 1 ea Lower rear: Solid back panel, standard
- 1 ea Left End Panel: Single cutaway with mirror interior lower, standard
- 1 ea Right End Panel: Single cutaway with mirror interior lower, standard
- 1 ea Lower Display: Single display deck, standard
- 1 ea Digital fahrenheit thermometer, standard

**ITEM 35 - WORK TABLE, STAINLESS STEEL TOP (1 REQ'D)****Advance Tabco Model FSS-309 Dimensions: 37(h) x 108(w) x 30(d)**

Work Table, 108"W x 30"D, 14 gauge 304 stainless steel top with 1-1/2"H rear up-turn, 18 gauge stainless steel adjustable undershelf, stainless steel legs & adjustable bullet feet, NSF

- 1 ea Model SS-2020-DL Deluxe Drawer, with keyed lock, 20"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides

**ITEM 36 - SHELVING, WALL MOUNTED (1 REQ'D)****Advance Tabco Model WS-15-108 Dimensions: 13.5(h) x 108(w) x 15(d)**

Shelf, wall-mounted, 108"W x 15"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 18/430 satin finish stainless steel, NSF (units 84" & longer have (3) support brackets)

**ITEM 37 - BLENDER CONTAINER RINSER (1 REQ'D)****Blendtec Model JRE-612 Dimensions: 7.5(h) x 8.8(w) x 20.5(d)**

(RRS) Rapid Rinser™ Station Complete Unit, magnetic switch, includes: Rapid Rinser™ sprayer & base, 6 ft. flexible nylon-reinforced tubing with 3/8" compression fitting for water hook-up (minimum 30psi recommended), stainless steel nozzle, 120° spray nozzle coverage

**ITEM 38 - UNDERCOUNTER REFRIGERATOR (1 REQ'D)****Atosa USA, Inc. Model MGF8401GRL Dimensions: 34.25(h) x 27.56(w) x 30(d)**

Atosa Undercounter Refrigerator, reach-in, one-section, 27-9/16"W x 30"D x 34-1/4"H, rear-mounted self-contained refrigeration, 7.15 cu. ft., (1) left hinged solid door, digital temperature control, 33° to 40°F temperature range, (1) adjustable shelf, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, 2" casters, R290 Hydrocarbon refrigerant, 1/7 HP, 115v/60/1-ph, 2.3 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation, ENERGY STAR®

1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 39 - REACH-IN UNDERCOUNTER FREEZER (1 REQ'D)****Atosa USA, Inc. Model MGF8405GR Dimensions: 34.5(h) x 27.5(w) x 30(d)**

Atosa Undercounter Freezer, reach-in, one-section, 27-1/2"W x 30"D x 34-1/2"H, rear-mounted self-contained refrigeration, 7.15 cu. ft., (1) right hinged solid door, digital temperature control, -8° to 0°F temperature range, (1) adjustable shelf, automatic evaporation, electric defrost, stainless steel interior & exterior, galvanized steel back, 2" casters, R290 Hydrocarbon refrigerant, 1/5 HP, 115v/60/1-ph, 1.8 amps, cord, NEMA 5-15P, cETLus, ETL-Sanitation

1 ea 2 year labor & parts warranty, 5 years warranty on compressor (continental USA only)

**ITEM 40 - ELECTRIC RESIDENTIAL RANGE (1 REQ'D)****Miscellaneous**

Provided by owner

**ITEM 41 - EXHAUST SYSTEM (1 REQ'D)****Captive Aire Model JOB #6689893**

1 ea 5424EX-2-PSP-F - 4ft 0" Long Exhaust-Only Wall Canopy Hood with 12" Wide Front Perforated Supply Plenum with Built-in 3" Back Standoff

- 430 SS Where Exposed

- Fire Cabinet on the Right Side 20.00" Width x 54.00" Length x 24.00" Height (Additional charges may apply for cabinet if not sold with fire system)

- FILTER - 16" tall x 20" wide Kleen-Gard Stainless Steel Baffle Filter with Handles and Bottom Hanging Hook, UL Classified



- L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture), Bulbs By Others
  - EXHAUST RISER - Factory installed 8" Diameter X 4" Height
  - SUPPLY RISER - 8"x 36" Supply Riser with Volume Dampers
  - 1/2 Pint Grease Cup New Style, Flanged Slotted
  - FIELD WRAPPER 17.00" High Front, Left, Right
  - Electrical Package Installation in Utility Cabinet by Plant.
  - RIGHT QUARTER END PANEL 23" Top Width, 0" Bottom Width, 23" High 430 SS
  - LEFT QUARTER END PANEL 23" Top Width, 0" Bottom Width, 23" High 430 SS
  - INSULATION FOR TOP OF HOOD
  - INSULATION FOR BACK OF HOOD
  - Parts required to mount riser sensor 6 inches beside riser. Sensor installed directly in line with the center of riser and in center of the plenum space front to back.
- 1 ea - BACKSPLASH 122.00" High X 104.00" Long 430 SS Vertical (Includes End Caps & Divider Bars)
- 1 ea TANK-SP-1 Tank Fire Suppression 4 gallon Fire System in Utility Cabinet (includes pre-piped hood(s) with electric detection, tank(s), 24 VDC release mechanism, fire system agent, pressurized tanks, and electric pull station). (Formerly CAS-EWC).
- Includes piping for hood: 1.
- Tank-based Fire Protection System equipped with Electronic Detection utilizing CORE board as a Listed Release Mechanism. Installed in Hood Utility Cabinet with integral hood prewire panel.
  - Pressure Switch - Monitors Tank Pressure, Supervised Signal, TANK FIRE SUPPRESSION
- 1 ea Model FIRE SYSTEM Field Final Included
- 1 ea Model EADU33H - EXHAUST FAN EADU33H High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 11-3/4" wheel.
- Exhaust Fan handles 720 CFM @ -0.600" wc ESP, Fan runs at 1434 RPM.
- Exhaust Motor: 0.333 HP, 1 Phs, 208 V, 60 Hz, 2.5 FLA, TEAO-ECM (Totally Enclosed Air Over Electronically Commutated Motor)
- Grease Cup for kitchen-duty centrifugal exhaust fans,
- Box Dimensions 17-1/8 L X 5-1/16 W X 3-3/4 H (20 Gauge) (Includes Down Spout)
- HINGE KIT - Standard Hinge kit for exhaust fan roof curbs. Includes Hardware to attach hinge to curb and hinge to base. Ships Loose. Used on Fans with wheels 20 inches or smaller. 12 GA Galvanized.
  - ECM Wiring Package for exhaust motors with PWM signal from ECPM03 prewire.
  - Multi-Conductor - Single Shielded Twisted Pair Cable, 18 AWG stranded (19x30) TC conductors, plenum, FEP insulation, overall shield (100% coverage), 20 AWG stranded TC

drain wire, FEP jacket. Priced per foot. For use with CORE Interlock Network, light dimming 0-10VDC reference signal, and PWM signal from ECPM03 to ECM.

1 ea - KEF - 1 Curb CRB19.5X22E On Fan #1 Flat Curb

- Vented Base for Curb

- Full Bottom Curb Corner. Base flange corners fully welded or staked by factory.

NOTE: WALL MOUNTED FAN - THRU WALL CURB IS FIGURED SO THE FAN CAN BE HINGED AS REQUIRED BY MECHANICAL CODE. WALL MOUNTED GREASE COLLECTION BOX BY OTHERS. RECOMMEND THE FOLLOWING PRODUCT BY DRIPLOC.

<https://www.driploc.com/distributors/product-tour/grease-containment-systems/deluxe-wall-mount-system/>

1 ea Model EA-A1-15D - SUPPLY FAN EA-A1-15D Untempered Supply Unit with 15" Mixed Flow Direct Drive Fan in Size #1 Housing

Supply Fan handles 576 CFM @ 0.400" wc ESP, Fan runs at 993 RPM.

Supply Motor: 1.000 HP, 1 Phs, 208 V, 60 Hz, 6.9 FLA, TEAO-ECM (Totally Enclosed Air Over Electronically Commutated Motor)

Side Discharge - Air Flow Right -> Left

- V-Bank for Size # 1 Modular Supply unit. EZ Metal Mesh Filters.

For indoor installation.

- Gravity Back Draft Damper, 16" wide x 18" high, Standard Galvanized Construction, 1 1/4" Rear Flange, for Size 1 Untempered Fan Housing (5181)

- Indoor Hanging Cradle For The Size 1 Untempered Unit. 2 HSA125 Hanging Isolators per Uni-Strut Included.

- "Insulation" for V-bank Intake Option.

- ECM Wiring Package for supply motors with PWM signal from ECPM03 prewire.

- Multi-Conductor - Single Shielded Twisted Pair Cable, 18 AWG stranded (19x30) TC conductors, plenum, FEP insulation, overall shield (100% coverage), 20 AWG stranded TC drain wire, FEP jacket. Priced per foot. For use with CORE Interlock Network, light dimming 0-10VDC reference signal, and PWM signal from ECPM03 to ECM.

1 ea Model ELECTRICAL SYSTEM SC-311110MA 3 Phase w/ control for 1 Exhaust Fan, 1 Supply Fan, Exhaust on in Fire, Lights out in Fire, Relay On/Off with Supply Fan, Fan(s) On/Off Thermostatically Controlled. Room temperature sensor shipped loose for field installation. INVERTER DUTY 3 PHASE MOTOR REQUIRED FOR USE WITH VFD. Includes 1 Duct Thermostat kit.

- Digital Prewire Lighting Relay Kit. Includes hood lighting relay & terminal blocks. Allows for up to 1400W of lighting each.

- Thermistor CABLE - 18/2 AWG GREEN WHITE, plenum rated. USED for thermistor duct stat. Per Foot Price.

1 ea Service Design Verification for Exhaust Fan

Service Design Verification for Hood

Service Design Verification for Standard Electrical Control Package

Service Design Verification for TANK Fire Suppression

Service Design Verification for Untempered Supply Fan

Service Design Verification Mileage Charge: (Excludes first 300.0 miles) 182.0 miles

Service Design Verification Minimum

Field Service Technician is responsible for one trip to site to ensure the above equipment is operating within design specifications. All equipment must be operational. Fire suppression system should be hooked-up and armed. Additional trips will result in charges to be covered by others.

TO BE COMPLETED BY MECHINCAL CONTRACTOR: Installation, ductwork, patching, all electrical field wiring, start-up & balance, gas or electric shutdown for fire system hook-up. Installation of wall covering to be preformed by GC

---