



Jones Gillam Renz Architects

Address		Contact	Web
730 N 9th St. Salina, KS 67401	1881 Main St., Suite 301 Kansas City, MO 64108	jgr@jgrarchitects.com (785) 827-0386	jgrarchitects.com

ARCHITECT'S SUPPLEMENTAL INSTRUCTIONS

JONES GILLAM RENZ DOCUMENT JGR 710

PROJECT:	The Reserves at Cobalt Circle New Development Brownsville, TN	Report No.	Six (6)
OWNER:	OPG Cobalt Circle Partners, LLC Dan Maximuk 250 N. Santa Fe Ave, Suite A Salina, KS 67401	Date	Dec. 22, 2025
CONTRACTOR:	MCP Group 3501 SW Fairlawn Rd. Topeka, KS 66614	Architect's Proj No.	24-3446

Contract For: General Construction
Mechanical, Electrical

The work shall be carried out in accordance with the following supplemental instructions issued in accordance with the Contract Documents without change in Contract Sum or Contract Time. Prior to proceeding in accordance with these instructions, indicate your acceptance of these instructions for minor change to the Work as consistent with the Contract Documents and return a copy to the Architect.

DESCRIPTION:

Contractor to make adjustments as needed and required per the modifications as indicated on attached drawings and in the below descriptions:

1. Structural Revisions:
 - a. Embedment lengths on Shear Walls have been revised.

Attachments:

1. Structural Sheets: S003, S501, S530


Issued by: Jones Gillam Renz Architects PO Box 2928, Salina, KS 67402
Maggie Gillam, Project Manager 785-827-0386 mgillam@jgrarchitects.com

Copies to:

MCP Group – Mike Maas, Cliff Holland, Tim Johnson, Kelli Meiers
OPG - Dan Maximuk, Amanda Klaus, Austin Kack
JGR Team - Maggie Gillam (JGR), Ryan Lies (LST), Cindy Senecal (McClure), Wesley Wooldridge (Renaissance), Michael Boerst (Heartland Energy)

NOTICE:
McClure Engineering Co. is not
responsible or liable for any issues,
claims, damages, or losses (collectively,
"Losses") which arise from failure to follow
these Plans, Specifications, and the
engineering intent they convey, or for
Losses which arise from failure to obtain
and/or follow the engineers' or surveyors'
guidance with respect to any alleged
errors, omissions, inconsistencies,
ambiguities, or conflicts contained
within the Plans or Specifications.

TENNESSEE CERTIFICATE OF
AUTHORITY
NO. 8231



CODY L. DAILEY
118933
EXP: 2/28/2026

I HEREBY CERTIFY THAT THIS
ENGINEERING DOCUMENT WAS
PREPARED BY ME OR UNDER MY
DIRECT PERSONAL SUPERVISION AND
THAT I AM THE ONLY
LICENSED STRUCTURAL ENGINEER
UNDER THE LAWS OF THE STATE OF
TENNESSEE.

No.	Description	Date
1	ASI 3 - WALL SCHED & TYP DETAIL	10/22/25
2	ASI 5 - BLDG C REVISION	12/05/2025
3	ASI 6 - SHEAR WALL SCHED REV	12/18/2025

PROJECT NUMBER 2024002664 SET ISSUE DATE 05/09/2025
ENGINEER DRAWN BY CHECKED BY
CAS CAS JTB

JONES GILLAM RENZ
COBALT CIRCLE
BROWNSVILLE, TENNESSEE

SCHEDULES
Autodesk DocID:202402864-JGR-CobaltCircle202402664-JGR-COBALT CIRCLE R24.M

DRAWING NO.
S003

FOUNDATION SCHEDULE		
Mark	Size	Reinforcing
F2.5	2'-6" x 2'-6" x 1'-0"	(3) #4 BARS Top & Bottom (Each Way)
F3.0	3'-0" x 3'-0" x 1'-0"	(3) #4 BARS Top & Bottom (Each Way)

Notes:
1. All footings must be centered on walls and columns U.N.O.

FLOOR AND ROOF SCHEDULE				
Type	Membrane/Sheathing	Fastening	Concrete/Topping	Reinforcing
Slab on Grade	12mil Vapor Retarder	Taped Edges	4" NW Concrete U.N.O.	6x6-W2.9xW2.9 WWF
Breezeway Floor	3/4" Plywood	Glue and Nail to Trusses w/10d @ 6/12	1 1/2" Lightweight Concrete Topping	---
Interior Floors	3/4" Plywood	Glue and Nail to Trusses w/10d @ 6/12	3/4" Gypcrete Topping	---
Roof	15/32" Plywood	10d @ 6/12 UNO	---	---

Notes:
1. Vapor barrier to be placed over compacted fill per general notes.
2. Plywood sheathing to be fastened per detail 2/S505. Individual panels to span a minimum of two framing bays.
3. Floor/Roof diaphragm are unblocked unless noted otherwise on plan.
4. Plywood to be APA rated Structural Grade 1 Material
5. See architectural drawings for full floor and roof assemblies including nonstructural elements.

WOOD WALL SCHEDULE				
Wood Wall Location	Wall Stud Size, number of plys, and spacing			Sheathing & Fastening U.N.O. (See Note 5)
	Level 1	Level 2	Level 3	
Exterior & Breezeway Walls	(1) 2x6 @ 24" o.c.	(1) 2x6 @ 24" o.c.	(1) 2x6 @ 24" o.c.	15/32" Structural wood sheathing fastened w/ 10d nails. 6" o.c. edge fastening, 12" o.c. field fastening
Single Bearing Walls Within Units	(3) 2x4 @ 24" o.c.	(2) 2x4 @ 24" o.c.	(1) 2x4 @ 24" o.c.	5/8" Gypsum wallboard fastened w/ 1 5/8" Type W screws. 7" o.c. edge fastening, 7" o.c. field fastening
Double Walls Separating Units	(2) 2x4 @ 24" o.c.	(1) 2x4 @ 24" o.c.	(1) 2x4 @ 24" o.c.	All Unit Separation Walls are Shear Walls. See Shear Wall Schedule for Sheathing & Fastening

Notes:
1. Wall stud spacing is to be per schedule unless noted otherwise.
2. All framing (studs and wood floor trusses) shall align floor to floor.
3. All roof trusses spanning exterior wall to corridor shall align with studs and framing below unless a triple top plate is provided.
4. Roof trusses less than 12'-0" long spanning exterior wall to girder truss are not required to align with studs and framing below.
5. Bottom sill plates at foundation to be fastened w/ 3/8"Ø x 6" Hill Kwik HUS-EZ Bolts @ 48" o.c. U.N.O.
6. Sill and top plates at all other levels to be fastened w/ (1) 16d nails with same spacing as wall studs U.N.O. on shear wall schedule.
7. Shear walls shall be sheathed & fastened per shear wall schedule.
8. Non-load bearing walls not shown, refer to architectural drawings.
9. All top plates are to be continuous. Splice per 3/S505.

10. U.N.O. bottom sill plates shall be (1) 2x member matching wall thickness, and top plates shall be (2) 2x members.
11. Where architectural drawings show 2x6 walls and structural drawings/schedule indicates 2x4 walls, architectural drawings shall control.

TYPICAL WALL HEADER SCHEDULE (WALLS SHOWN ON FRAMING PLANS ARE WALLS BELOW)						
Header Type	Header	Kings/Jacks				
		Level 1	Level 2	Level 3		
HA	(3) 2x8	(1) 2x6 K	(1) 2x6 J	(1) 2x6 K	(1) 2x6 J	(1) 2x6 K
HB	(3) 2x8	(1) 2x6 K	(2) 2x6 J	(1) 2x6 K	(2) 2x6 J	
HC	(3) 1 3/4" x 7 1/4" LVL				(1) 2x6 K	(2) 2x6 J
HD	(2) 2x8	(1) 2x4 K	(2) 2x4 J	(1) 2x4 K	(2) 2x4 J	(1) 2x4 K
HE	(2) 2x10	(1) 2x4 K	(2) 2x4 J	(1) 2x4 K	(2) 2x4 J	
HF	(3) 2x10	(1) 2x6 K	(3) 2x6 J			


Notes:
1. See 5/S505 for typical opening framing.
2. Coordinate all dimensions and elevations with architectural drawings.
3. Provide double sills below windows at openings greater than 6'-0" in length.
4. All Laminated Strand Lumber (LSL) shall be stress class 1.3E-1700Fb.
5. All Laminate Veneer Lumber (LVL) shall be stress class 2.0E-2600Fb.

WOOD SHEAR WALL SCHEDULE							
Mark	Level	Sheathing/ Fastener Layout	Post	Hold-Down	Base Connection	ASD Truss Drag Load plf	
						0.6 Wind	0.7 Seismic
SW1	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	144	92
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MST60 (46) .162 x 2 1/2 NAILS	(2) 16d nails @ 12" o.c.	252	200
	Level 1	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(3) 2x6	HDU14-SDS2.5 w/ (36) 1/4"Øx2-1/2"SDS Screws 1"Ø Anchor Rod 8" Embed	(1) HILTI KH-EZ 3/8"Øx 6" @ 12" o.c.	475	308
SW2	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	144	92
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MST60 (46) .162 x 2 1/2 NAILS	(2) 16d nails @ 12" o.c.	252	200
	Level 1	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(3) 2x6	HDU14-SDS2.5 w/ (36) 1/4"Øx2-1/2"SDS Screws 1"Ø Anchor Rod 8" Embed	(1) HILTI KH-EZ 3/8"Øx 6" @ 12" o.c.	353	254
SW3	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	119	76
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(2) 2x6	MST37 (22) .162 x 2 1/2 NAILS	(2) 16d nails @ 24" o.c.	208	165
	Level 1	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(3) 2x6	HDU8-SDS2.5 (20) 1/4"Øx2-1/2"SDS Screws 5/8"Ø Anchor Rod 8" Embed	(1) HILTI KH-EZ 3/8"Øx 6" @ 24" o.c.	292	210
SW4	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MSTC37 (22) .162 x 2 1/2 NAILS	(2) 16d nails @ 24" o.c.	205	131
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(2) 2x6	MST60 (46) .162 x 2 1/2 NAILS	(2) 16d nails @ 12" o.c.	357	284
	Level 1	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 4" Edge fastening	(3) 2x6	HDU11-SDS2.5 (30) 1/4"Øx2-1/2"SDS Screws 1"Ø Anchor Rod 8" Embed	(1) HILTI KH-EZ 3/8"Øx 6" @ 12" o.c.	501	360
SW5	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x4	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	72	46
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x4	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	125	100
	Level 1	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x4	HDU2-SDS2.5 (14) 1/4"Øx2-1/2"SDS Screws 5/8"Ø Anchor Rod 8" Embed	(1) HILTI KH-EZ 3/8"Øx 6" @ 24" o.c.	176	126
SW6	Level 3	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MSTC28 (16) .148 x 3 1/4 NAILS	(2) 16d nails @ 24" o.c.	67	137
	Level 2	(1) Sided, Wood Structural Panels - S1 - 15/32" 10d Nail, 6" Edge fastening	(2) 2x6	MST60 (46) .162 x 2 1/2 NAILS	(2) 16d nails @ 12" o.c.	107	298
	Level 1	(1) Sided					




M^CCLURETM


2001 W Broadway
Columbia, MO 65203
P 573-814-1568




1 EXTERIOR SHEAR WALL SECTION AT HOLD DOWN
S501 1" = 1'-0"



3 FOUNDATION SECTION AT BREEZEWAY
S501 1" = 1'-0"



2
S501 INTERIOR SHEAR WALL SECTION AT HOLD DOWN
1" = 1'-0"




4 FOUNDATION SECTION AT POST IN BREEZEWAY EXTERIOR WALL
S501 1" = 1'-0"

JONES GILLAM RENZ COBALT CIRCLE

FOUNDATION DETAILS

NOTICE:
McClure Engineering Co. is not responsible or liable for any issues, claims, damages, or losses (collectively, "Losses") which arise from failure to follow these Plans, Specifications, and the engineering intent they convey, or for Losses which arise from failure to obtain and/or follow the engineers' or surveyors' guidance with respect to any alleged errors, omissions, inconsistencies, ambiguities, or conflicts contained within the Plans or Specifications.

TENNESSEE CERTIFICATE OF AUTHORITY
NO. 8231



CODY L. DAILEY
118933
EXP: 2/28/2026

I HEREBY CERTIFY THAT THIS ENGINEERING DOCUMENT WAS PREPARED BY ME OR UNDER MY DIRECT PERSONAL SUPERVISION AND THAT I AM A FULLY LICENSED STRUCTURAL ENGINEER UNDER THE LAWS OF THE STATE OF TENNESSEE.

No.	Description	Date
1	ASI 6 - SHEAR WALL SCHED REV	12/18/2025

PROJECT NUMBER 2024002664 SET ISSUE DATE 05/09/2025
ENGINEER DRAWN BY CHECKED BY
CAS CAS JTB

JONES GILLAM RENZ
COBALT CIRCLE
BROWNSVILLE, TENNESSEE
SHEAR WALL DETAILS
Autodesk DocId:202402664 - JGR - Cobalt Circle/202402664 - JGR - COBALT CIRCLE R24.1M

